



# GLOBAL INDUSTRIAL PRODUCTS, INC.

3338 West Lake, Glenview, IL 60025, USA  
 Tel: 847.901.4040 • Fax 847.901.4036 • E-mail sales@globalepower.com  
 Web site: www.globalepower.com

## SCM Series Gaming Meter “Hard Counters”

### Features:

SCM Series Gaming Meters are non-resettable, miniature, electromagnetic, compact, lightweight, and energy efficient. They are built for long life and a wide variety of uses. High accuracy and reliability result in a maximum counting speed of 15 cps.

### Uses:

Gaming, vending, and office machines as well as any other monitoring applications.

### Part Number Scheme

SCM-□□□□□□

□ Mounting SA, PA, BA, BB  
 □ Digit (6 or 7)  
 □ Operating Voltage (05,06,12,24)

SCM-□□□□0SA  
Panel Mount (Snap-In)



SCM-□□□□0PA  
Back of Panel Mount (2 screw)



SCM-□□□□0BA  
Bottom Screw Down



SCM-□□□□0BB  
PCB Mount

<b>Specifications</b>	Subject to change without notice.	Power consumption: < 1W.	On-time: min 33.3 msec, max continuous.	Life: > 10,000,000 counts.
Number of digits: 6 or 7.		Counting input: Voltage input, one pulse per count.	Withstand Voltage: 1 min or longer @ 1500 VAC.	Operating temperature: -10 to +60° C.
Digit size: 2.2 mm x 1.3 mm with magnifying window. white on black.		Voltage ripple: <10%.	Insulation resistance: 100 MΩ or more/500 VDC.	Operating humidity: 10 to 95% RH.
Case: Black ABS resin.		Maximum counting speed: 15 cps @ make ratio of 1:1.	Weight: SA =23g, PA =20G, BA =18g, BB =16g.	Initial set value: 999500, 9999500 or optional value.
Operating voltage: 5, 6, 12, & 24 VDC. Standard AC voltages and optional diode are available.		Allowable variable voltage: ± 10% of rated operating voltage.	Vibration resistance: JIS-C4555 (16.7Hz, 4mm, 1 hour in the x, y, z directions respectively).	Impact resistance: JIS-C4555 (300m/s <sup>2</sup> , five times in the in x, y, z directions respectively).

